REV. 01

RIDGEGUIDE MODEL # CHART
MM & MW SERIES

Model # ex. M W T R180 B S L 2 A 3

ENVIRONMENT	
M	SHELTERED
W	OUTDOOR
S	SEALED

TTL OPTIONS	
OMIT	NO TTL
T	HIGH LOGIC
V	SINGLE LOGIC
P	POE

WR SIZE
R110
R180
R200
R250
R350
R475
R500
R580
R650
R750

SWITCHING OPTIONS	
A	SPDT - 3 PORT
B	DPDT - 4 PORT
C	SP3T - 4 PORT
D	DP4T - 4 PORT

VOLTAGE OPTIONS	
8	12 VDC
9	15 VDC
7	24 VDC
2	28 VDC
4	48 VDC
1	115 VAC

INTERFACE, OVERRIDE OPTIONS	
1	CYLINDRICAL CONNECTOR, no OVRD
3	CYLINDRICAL CONNECTOR, Ø1" KNOB
4	CYLINDRICAL CONNECTOR, Ø1.44" KNOB
5	CYLINDRICAL CONNECTOR, KNOB COVER w/ VIEWING WINDOW
6	D-SUB, MALE, no OVRD
7	D-SUB, MALE, w/KNOB
9	SOLDER TERMINALS, no OVRD

FLANGE OPTIONS	
S	COVER
SM	COVER, METRIC
U	GROOVE
UM	GROOVE, METRIC

DRIVE OPTIONS	
L	LATCHING
P	PULSE LATCHING
F	FAILSAFE
T	MANUAL
N	LATCHING (+) COM
NP	PULSE LATCHING (+) COM

ELECTRICAL CIRCUIT OPTIONS	
OMIT	1 SET INDICATORS
A	NO INDICATORS
B	2 SETS INDICATORS
C	3 SETS INDICATORS
D	4 SETS INDICATORS
E	1 SET INDICATORS w/ INHIBIT CIRCUIT CLOSED DURING SWITCHING
F	2 SETS INDICATORS w/ INHIBIT CIRCUIT CLOSED DURING SWITCHING
G	3 SETS INDICATORS w/ INHIBIT CIRCUIT CLOSED DURING SWITCHING
H	1 SET INDICATORS w/ INHIBIT CIRCUIT OPEN DURING SWITCHING
J	2 SETS INDICATORS w/ INHIBIT CIRCUIT OPEN DURING SWITCHING